



PRESENTED BY

2026 Rules

Version 2026.1

Released January 22, 2026

Significant **additions or changes** and **deletions** are highlighted.

<u>General Rules</u>	(1)
<u>Stock Class</u>	(3)
<u>Street Class</u>	(5)
<u>Touring Class</u>	(5)
<u>Unlimited Class</u>	(5)
<u>Modification Points</u>	(6)
<u>Chassis</u>	(6)
<u>Tires</u>	(6)
<u>Suspension</u>	(7)
<u>Engine Mechanical & Drivetrain</u>	(7)
<u>Engine Tuning</u>	(8)
<u>Aero: Splitters/Lips</u>	(8)
<u>Aero: Wings/Spoilers</u>	(9)
<u>Aero: Other</u>	(9)
<u>Weight Reduction</u>	(9)
<u>Safety</u>	(9)

Introduction

Welcome to 86 Challenge **Presented by Yokohama**. Drivers of all skill levels are welcome and there is no charge to participate.

See 86challenge.us for more information, including schedule, historical results, and forms for registering for the **RaceTreads.com Championship Cash Prize** and **Yokohama Tire Contingency** programs.

Feel free to raise questions/clarifications in the #regulations channel on our [Discord Server](#) or on [Facebook](#). Throughout this document, OE refers to Original Equipment, as delivered from the factory.

1. General Rules

1.1. Chassis must be one of the following (hereafter referred to by its *Designation*):

Designation	Chassis
Gen. 1	<ul style="list-style-type: none">2012–2016 Scion FR-S2012–2020 Subaru BRZ2017–2020 Toyota 86
Gen. 2	<ul style="list-style-type: none">2022+ Subaru BRZ2022+ Toyota GR86

1.2. Registration

- 1.2.1. Drivers must register for 86 Challenge prior to the start of each event (separate from buying entry with the trackday organizer). The registration form is made available on 86challenge.us prior to each event. In case of multiple submissions, the last submission will be used.
- 1.2.2. Late registrations may be accepted on a case-by-case basis, but a driver registering late may not change to a different class from their previous event or previous registration for the same event.
- 1.2.3. Drivers may share a car. Each driver must register separately and indicate their class, run group, and with whom they are sharing a car. Drivers sharing a car may not switch drivers during a single session.

1.3. Timing

- 1.3.1. The following timing methods are accepted (see table below). Priority is given from top to bottom if more than one method is available for a given lap:

Timing Method	Time Penalty (s)
Official timing transponder	0.0
10 Hz or greater GPS lap timer (e.g. AiM, Garmin Catalyst, smartphone app with external GPS)	0.2
1 Hz or greater GPS lap timer (e.g. smartphone app with built-in GPS)	0.5
Unedited onboard video (may be accepted for a driver's first event only)	0.5

- 1.3.2. **Tiebreaker:** If multiple competitors have identical times in an event, the tie is broken by comparing each driver's second fastest lap, then third fastest lap, and so on.

1.4. Scoring

- 1.4.1. Points are awarded at the end of each event according to the table below:

Finishing Position	Points
1st	10
2nd	7
3rd	5
4th	4
5th	3
6th	2
7th+	1

- 1.4.2. Separate points tallies are used to track Championship Standings and Tire Contingency points:

Type	Definition
Total Points	The sum of a driver's points earned from all events
Championship Points	The sum of a driver's points earned from their 7 best finishes
Tire Points	The sum of a driver's points earned satisfying the terms of the Yokohama Tire Contingency Program, up to a maximum of 80 points

- 1.4.3. **Changing Classes:** If a driver changes classes during a season, they can choose to:

- Keep the *Championship Points* earned in their previous class and not earn *Championship Points* in the new class; or,

- Forfeit the *Championship Points* earned in their previous class and earn *Championship Points* in the new class.

1.4.4. The per-class standings are determined by *Championship Points* (most points wins).

1.4.5. **Tiebreaker:** Championship ties are broken via finishing position countback: The competitor with the most 1st place finishes wins. If still tied, the countback moves to 2nd place, 3rd place, and all subsequent finishing positions. Only the best 7 results per driver are considered. If still tied, the competitor who held a lead last wins.

1.5. In-Season Rule Changes

1.5.1. All rule changes will be announced on our [Discord Server](#) and [86challenge.us](#). Announcements will include the date on which changes become effective.

1.5.2. Changes which make the rules more *restrictive* will be announced 60 days before enforcement.

1.5.3. Changes which make the rules more *permissive* may be enforced immediately.

1.6. Protests

1.6.1. A competitor may protest the results of an event to the Rules Board if they believe a competitor was out of compliance with the rules.

1.6.2. The Rules Board will review the protest and may move a competitor to a different class or invalidate their results for one or more events.

1.6.3. Results are final and no further protests will be accepted once the season-ending award ceremony has begun.

2. Stock Class

Designed to keep costs to a minimum and be attractive to drivers with nearly-stock vehicles.

2.1. Vehicles in this class are only allowed performance modifications included in this section.

2.2. Time Handicap: In order to balance performance between Gen. 1 and Gen. 2 cars, a time handicap will be added to Gen. 2 lap times, according to the table below. The same handicaps are used whether the track is run in the clockwise or counterclockwise direction. For any tracks/configurations not listed below, the closest comparable track configuration will be used.

Track	Time Handicap (s)
Buttonwillow Classic #1, #25	2.5
Buttonwillow Classic #13	2.0
Buttonwillow Circuit	2.5
Laguna Seca	2.5
Sonoma	2.5
Thunderhill 5-mile	4.0
Thunderhill East	2.5
Thunderhill West	1.5

2.3. Engine & Powertrain

2.3.1. Engine software/firmware must be unmodified.

2.3.2. Oil coolers, catch cans, accumulators, and/or sump changes (excluding dry sump systems) are allowed.

2.3.3. Gen. 2 only: intake charcoal filters shall be present and unaltered.

2.3.4. Any pump gasoline (including blending high-octane pump gasoline) is allowed.

2.3.5. Intake resonators may be removed.

2.4. Wheels

- 2.4.1. Wheels must have a maximum width of 8.0 in.
- 2.4.2. Wheel spacers are allowed.
- 2.4.3. Aftermarket lug nuts and wheel studs are allowed.

2.5. Tires

- 2.5.1. Tires must be one of the following:

Models	Sizes
Yokohama Advan Apex V601	• 225/45R17
GT Radial Champiro SX2 or Champiro HPY*	• 215/45R17 • 225/45R17
Michelin Primacy HP or Primacy 4 (OE)**	• 215/45R17
Michelin Pilot Sport 4 (Gen. 2 OE)**	• 215/40R18

* GT Radial tires are allowed until March 31, 2026

** OE tires are only allowed for a competitor's first 2 86 Challenge events and are ineligible for Tire Points.

2.6. Alignment

- 2.6.1. Front camber shall not exceed (be more negative than) -2.5 degrees. Front camber may be adjusted using only the following parts:

Description	Allowed Parts
Crash bolts (i.e. OE 14 mm lower bolt used in upper position)	• Subaru 901000394 • Toyota SU003-02818
Upper camber bolts	• SPC 81280 • Whiteline KCA416
Lower camber bolts	• Eibach 5.81305K • SPC 81305 • Whiteline KCA414
Front strut mounts	• Pedders PED-580096 • Whiteline KCA335

- 2.6.2. Rear camber shall not exceed -2.0 degrees. Rear camber may be adjusted using only the following parts:

Description	Allowed Parts
OE-style, adjustable, stamped steel rear lower control arms	• Moog RK100136 • SPC 67660 • Whiteline KTA216A

- 2.6.3. Toe angle may be adjusted without limitation.
- 2.6.4. Cutting or bending of any vehicle sheet metal or suspension components to change alignment or ride height is not allowed.

2.7. Aero

- 2.7.1. STI lip and TRD lip are not allowed.
- 2.7.2. Gen. 1 BRZ tS wing is not allowed.
- 2.7.3. Gen. 2 ducktails (OE or equivalently-sized) are allowed.

2.8. Safety

- 2.8.1. Any safety device may be used.
- 2.8.2. Cars may be equipped with aftermarket safety systems (bucket seats, racing harnesses, neck restraint system, full or half roll cage, etc.), as long as the total curb weight of the

car remains above 2,800 lbs without driver and with a full tank of fuel. Removing interior trim is allowed only as necessary to install the safety systems. The car must be weighed at a location approved by the Rules Board before it is allowed to enter Stock Class.

2.9. Misc

- 2.9.1. Any brake fluid, brake pads, brake rotors, brake ducting, and/or big brake kits are allowed.
- 2.9.2. Replacing OE parts with newer/older OE parts is allowed (e.g. dampers, sway bars, etc).
- 2.9.3. No lightweight replacement parts are allowed (e.g. battery or lighter-than-OE trunk).
- 2.9.4. Removal of parts is prohibited, except the following: spare tire, floor mats, and included tools.
- 2.9.5. The following unmodified OE-Replacement dampers are allowed: Bilstein B6, KYB Excel G, or **Tein EnduraPro (Non-Adjustable)**.
- 2.9.6. Aftermarket cat-back exhaust with a weight greater than 32 lbs or axle-back with weight greater than 19 lbs are allowed. OE catalytic converters must be retained and unmodified.

3. Street Class

Allows moderate modification flexibility and balances competition between generations through Modification Points.

- 3.1. Drivers are allotted a maximum of 3 [Modification Points](#).

- 3.2. Any performance modification not listed in [Modification Points](#) is prohibited.

- 3.3. Minimum weight is 2,800 lbs without driver and with a full tank of gas.

3.4. Wheels

- 3.4.1. Wheels must have a maximum width of 9.0 in.

3.5. Tires

- 3.5.1. Tires must be one of the following:

Models	Sizes
Yokohama Advan Apex V601	<ul style="list-style-type: none">• 225/45R17• 245/40R17
GT Radial Champiro SX2 or Champiro HPY*	<ul style="list-style-type: none">• 215/45R17• 225/45R17• 245/40R17
Michelin Primacy HP or Primacy 4 (OE)**	<ul style="list-style-type: none">• 215/45R17
Michelin Pilot Sport 4 (Gen. 2 OE)**	<ul style="list-style-type: none">• 215/40R18

* **GT Radial tires are allowed until March 31, 2026**

** OE tires are only allowed for a competitor's first 2 86 Challenge events and are ineligible for Tire Points.

4. Touring Class

Allows significant modification freedom and many more tire choices.

- 4.1. Drivers are allotted a maximum of 7 [Modification Points](#).

- 4.2. Maximum tire section width is 255 mm.

- 4.3. Minimum weight is 2,750 lbs with driver and full tank of gas.

5. Unlimited Class

Allows unconstrained builds to achieve the ultimate 86 lap times. For people who don't like rules!

5.1. Anything goes!

6. Modification Points

This section applies only to Street Class and Touring Class.

Chassis

Points	Chassis
0	Gen. 1 (2013–2020 model years)
2	Gen. 2 (2022+ model years)

Tires

Any tire not on this list is automatically 6pts

Discontinued tires are allowed and inherit the points of their successors

Points	Modifications	
-1	<ul style="list-style-type: none">Yokohama Advan Apex V60117" GT Radial SX2*GT Radial HPY	<ul style="list-style-type: none">Michelin Primacy HPMichelin Primacy 4
0	<ul style="list-style-type: none">Michelin Pilot Sport 4	
1	<ul style="list-style-type: none">18" GT Radial SX2	
1.5	<ul style="list-style-type: none">Yokohama Advan Neova AD09	
2	<ul style="list-style-type: none">Armstrong Blu-Trac RaceBFGoodrich g-Force Rival+Continental ExtremeContact Force (ECF)Continental ExtremeContact Sport (ECS)Falken Azenis RT615K+Federal 595 RS-RRGoodyear Eagle F1 Supercar 3GT Radial SX2 RSHankook Ventus RS-4	<ul style="list-style-type: none">Maxxis Victra VR-1Michelin Pilot Sport 4SMichelin Pilot Sport Cup 2 (180TW)Michelin Pilot Sport Cup 2 ConnectNankang NS-2RNitto NT01Nitto NT05Toyo Proxes R888R
2.5	<ul style="list-style-type: none">Yokohama Advan A052Falken Azenis RT660+	<ul style="list-style-type: none">Kumho Ecsta V730Maxxis Victra VR2
3	<ul style="list-style-type: none">BFGoodrich g-Force Rival SBridgestone Potenza RE71RZGoodyear Eagle F1 Supercar 3RHoosier TrackAttack Pro	<ul style="list-style-type: none">Maxxis Victra RC-1Nankang AR-1Nankang CR-SVitour Tempesta P1
5	Treadwear 40-99	
6	Racing slicks or any tire not listed above	

* 17" GT Radial SX2 will be reclassified as 0 pts after March 31, 2026.

Suspension

Free Modifications

- Any alignment bolt/kit
- Any altered suspension mounting points and suspension lengths
- Any bolt-on chassis bracing
- Any spherical bushings, including strut top mounts
- Any sway bars
- Any wheel spacers

Take points for ONE of the following:

Points	Modifications
0	Unmodified OE or OE-Replacement* dampers with OE springs** and bump stops
0.5	Unmodified OE or OE-Replacement* dampers with aftermarket/modified springs and/or bump stops
1.0	Any other dampers without remote reservoirs*** with any springs and bump stops
1.5	Any other dampers with remote reservoirs*** with any springs and bump stops

* **OE-Replacement** Must be one of the following: Bilstein B6, KYB Excel G, or **Tein EnduraPro (Non-Adjustable)**

** **OE springs** STI and TRD lowering springs are not considered OE

*** **Remote reservoirs** Including piggybacks or other volume-expanding devices

Engine Mechanical & Drivetrain

Free Modifications

- Any cat-back exhaust
- Any drop-in replacement air filter for OE intake
- Any pump gasoline (including blending high-octane pump gasoline)
- Any radiator, oil cooler, oil catch can, oil pan baffle, and/or modified sump
- Any transmission cooling or diff cooling system
- Gen. 2 charcoal airbox filter removal
- Removal of intake resonators

Take points for EACH applicable row:

Points	Modifications
0.5	Aftermarket intake, header, front-pipe, overpipe, and/or any removal of OE catalytic converter
0.5	Lighter-than-OE rotational inertia flywheel, clutch, and/or driveshaft
0.5	Aftermarket limited slip differential
1	Aftermarket transmission
2	FA20 to FA24 engine swap
4.5	Forced induction
TBD	Any other engine swap (contact Rules Board for individual engine swap classification)

Engine Tuning

Octane ratings below use (RON+MON)/2 or AKI. This is the octane number displayed at the pump in the US.

Take points for ONE of the following:

Points	Modifications
0	OE engine tune
0.5	Engine tune for 93 octane gasoline or lower
1.5	Naturally aspirated engine tune for >93 octane gasoline or >15% ethanol content
2.5	Forced induction engine tune for >93 octane gasoline or >15% ethanol content




Figure 1: Leading and trailing edges are measured as a straight line to the ground




Figure 2: Leading and trailing edges follow the contour of the vehicle

Aero: Splitters/Lips

Take points for ONE of the following:

Points	Modifications
0	No aero modifications or any device extending up to 50 mm in any direction from the bottom leading edge of the bumper (including STI lip and TRD lip)
1	Any device extending up to 75 mm in any direction from the bottom leading edge of the bumper
1.5	Any device extending up to 125 mm in any direction from the bottom leading edge of the bumper
3	Any device extending greater than 125 mm in any direction from the bottom leading edge of the bumper

Aero: Wings/Spoilers

Free Modifications

- OE rear spoiler
- OE wing (except Gen. 1 BRZ tS wing)
- Any aftermarket spoiler less than 60 mm in height

Take points for EACH applicable row:

Points	Modifications
0.5	Aftermarket rear spoiler greater than 60 mm in height
1	SARD LSR, Gen. 1 BRZ tS wing, or any wing with maximum width of 1400 mm, maximum stand height of 200 mm , maximum chord length of 200 mm, and no added gurney flap
1.5	APR GTC-200, Voltex Type 12, Voltex Type 1S, or any wing with maximum width of 1460 mm, maximum stand height of 245 mm , and maximum chord length of 250 mm
2	Any wing wider than 1460 mm, higher than 245 mm , or with a chord length greater than 250 mm

Aero: Other

Free Modifications

- Rear diffuser between the rear axle and the rear trailing edge of the bumper
- Rear spats
- Side skirts

Take points for EACH applicable row:

Points	Modifications
0.5	Canards, dive planes, hood vents, fender vents, and/or vertical deviations on splitters
0.5	Any underbody aero modifications between the front and rear axles and/or rear diffuser extending backward beyond the rear bumper trailing edge

Weight Reduction

Free Modifications

- Any lightweight battery

Take points for EACH applicable row:

Points	Modifications
1	Removal of any interior trim pieces or seating not required for installation of a roll cage

Safety

Free Modifications

- Any brake fluid, brake pads, brake rotors, brake ducting, and/or big brake kit (BBK)
- Any in-cabin safety equipment
- Any lug nuts and wheel studs